

## 1. Applications

EUROFLEX® Half Ball is used as seating and communication islands in playing areas and also as playing components.

EUROFLEX® Half Ball is manufactured by an environment-friendly process and can be recycled as process raw material at the end of their service life.

## 2. Material Standard SBR Ball

Rubber granulate: granulated recycled rubber  
Binding agent: MDI polyurethane

## 3. Characteristics

Colour: red, green, grey or black  
(minor colour variation possible)  
Surface: smooth with open pores

## 4. Dimensions / Tolerances

Diameter: approx. 345, 500, 695 mm  
Weight: approx. 9,2 kg, 28,0 kg, 75,2 kg  
Tolerances: +/- 0,8 %  
Dimension steel anchors: Ø 42,8 mm, length approx. 750 mm

## 5. Material Ball with EPDM topping

Rubber granulate: granulated recycled rubber  
Binding agent: MDI polyurethane  
Topping: Coloured EPDM rubber granulate  
Colour:



All information without guarantee, subject to change. The Data Sheet is not subject to any change service.  
Each current and valid from can be recalled at [www.kraiburg-relastec.com/euroflex](http://www.kraiburg-relastec.com/euroflex)

## 6. Characteristics

Surface: minor colour variation possible  
smooth with open pores

## 7. Dimensions / Tolerances

Diameter: approx. 345, 500, 695 mm  
Weight: approx. 10,2 kg, 30,0 kg, 83,0 kg  
Tolerances: +/- 0,8 %  
Dimension steel anchors: Ø 42,8 mm, length approx. 750 mm

## 8. Test Data

Production facility inspection  
EN 1176-1:2017  
Migration of certain elements: in accordance with DIN EN 71-3  
Fire resistance: Class E, DIN EN 13501-1, 2010  
Chemical resistance: conditionally resistant to acids and bases

## 9. Installation

Install EUROFLEX® Half Ball by inserting their steel anchors.  
Note the complete installation instruction.